

## Shower Toilet rimless, wall-hung with remote control, with seat and cover 82069.1



### TECHNICAL DATA

Order no.	82069.1	Power supply & consumption	Power consumption in use max. 1'400 W Power consumption in standby (boiler at ECO or OFF, LED display OFF) < 1 W Protection rating IPX4 Protection class I
Certified to	CE, IPX4, EN 13077, SVGW Drinking water standards EN 1717	Weight	40,0 kg
matching for	LIS CW2 Concealed frame with cistern for shower toilets, order no. 89466.1	Accessories incl.	Touch screen remote control, with batteries and wall holder Carbon filter, descaling agent, splash protection User manual
Specifications	Shower Toilet rimless, wall-hung, with ceramic surface refinement LCC Washdown, flushing from 6 l to 4.5 l, concealed fixation Controller with rotary button for shower function	Mounting acc. incl.	Inlet and outlet pipes, fastening kit M12 with mounting plate, sound insulation set (DIN 4109) and water connection set for shower toilet Mounting instruction
Functions	Rear shower and lady shower adjustable in pressure, position and temperature, shower duration range 15-20-25 sec Oscillating and pulsating cleaning mode 4 programmable user profiles Self cleaning of nozzle before and after every use Automatic air purifier with active carbon filter Descaling programme Thermal cleaning heats up the entire water-carrying system with water heated to 70°C Light with signaling feature	Mounting acc. excl.	Adapter plate for Cleanet Riva Shower Toilet, order no. 89469.0 Stone screw fastening kit M12
Water pressure & temperature	Shower 7 pressure levels Flow rate ca. 4.3 l/min, Power mode ca. 5.6 l/min, Lady shower ca. 2.5 l/min Shower 7 temperature level	Colours	400 – White LCC
Water inlet	concealed, G 3/8" Water flow pressure range 0.1 to 1 MPa (1-10 bar) Operating temperature range +5 to +40 °C	<b>SPECIFICATION TEXT</b> Shower Toilet rimless, wall-hung, washdown Laufen CLEANET RIVA toilet pan sanitary ceramic, with ceramic surface refinement LCC WC seat and cover Duroplast, removable, with lowering system CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717 min. 4.5/3-l-flush, dimensions 395 x 600 x 505 mm, concealed fixation Special feature: Touch screen remote control, rear shower and lady shower, with adjustable water pressure, temperature and nozzle position, oscillating and pulsating cleaning mode, integrated self cleaning nozzle before and after every use, integrated odour filter, light with signaling feature, programmable user profiles, water supply and power supply concealed Order no. 82069.1	
Outlet	DN 110 mm horizontal		
WC seat and cover	Duroplast, removable, with lowering system		
Power supply & consumption	concealed Rated voltage 220 to 240 V, 50/60 Hz Direct connection by NYM cable possible		

### TECHNICAL DRAWINGS / S 1 : 20

